Technical data sheet

Updated: 03/2013

Peramin® SRA 40

Shrinkage reducing agent

- Reduces the risk of cracking
- Reduces the curling





Peramin® SRA 40

Shrinkage reducing agent

Description

Peramin® SRA 40 is a polyols based additive in powder which reduces mainly drying shrinkage.

Compatibility

Peramin® SRA 40 is compatible with the majority of admixtures used in drymix mortars and specially with **Peramin® CONPAC** and **SMF**.

Laboratory trials are advised before any industrial use.

Application

Dry-mortar industry

Concrete

Specifications

	Datas	Methods
Appearance	Powder	Visual
Active Matter (%)	58 - 64	PEROU012*
Bulk Density	0.55 - 0.75	PEROU007*
Granulometry (% > 600 µm)	< 3%	PEROU010*
pH (5% solution)	6 - 8	PEROU008*

Updated: 03/2013

Dosage

Depending on the application, the dosage of **Peramin® SRA 40** varies from 1% to 5% by weight of hydraulic binder.

Packaging

· Pallet of 20 sacks of 25 kg

Conditions of storage

- Shelf life: 12 months in unopened bags, between 5°C and 35°C.
- The product may absorb moisture and should be stored in dry area.
- Opened bags should be carefully resealed and used within a short period of time.

Peramin warrants that the products comply with the specifications stated herein to the exclusion of any other warranty, express or implied. Peramin makes no representation or warrantly of any kind, either express or implied, as to the merchantability or fitness for a particular purpose or use of the products. The warranty shall be limited to the replacement of the non-conforming products or, at Peramin's option, the refund of the purchase price.

Any technical advice, recommendations or information are given based Peramin's current knowledge and experience of the products and are deemed to be accurate. However, Peramin undertakes no liability or responsibility of any kind in respect thereof. Users are invited to check that they have the latest version of this document.



^{*} Internal methods